

For product reference prefix : HZA (to suit 44mm door ONLY)

Intastop Ltd can take no responsibility for incorrect operation of Hinges that are not fitted as per directed in these instructions

IMPORTANT NOTE: This product must be fitted in conjunction with the R100 Concealed door Closer

1. Position the door leaf of the hinge on the door. Ensure the door leaf alignment is seated along the full length of the door edge and the top edge of the door leaf is flush with the top edge of the door and that the anti ligature tips are at the door head
2. If existing gaps are not sufficient to take the frame leaf of the hinge, plane the lipping on the hanging stile as necessary
3. Mark and drill for 12nr. 1 ½" x 10 csk tamper proof screws. Drill 3mm-3.5mm pilot hole **but do not install**
4. With the hinge leaves open position the hinge against frame jamb. Ensure the leaf alignment flange is tight against the face of the frame. Allow 3mm maximum gap between head of the frame & top of the hinge for door clearance. Mark and drill the top two holes for 10csk tamper proof screws, drill 3mm-3.5mm pilot hole **but do not install**
5. Mark in the frame where to rebate for locking system then rebate. Drill into face of frame enabling key to be located in lock.
6. Screw the door leaf portion of the hinge to the door
7. Position door at 90 to the frame and install the top two screws in the frame leaf
8. Close door and check for proper swing & clearance. Adjust if required
9. Mark and drill remaining holes, drill 3mm-3.5mm pilot holes for 10csk Phillips head screws and attach to frame
10. The lock can be adjusted by means of the screw on the faceplate